



WMC8943VC.S

Professional washing machines

General description

Product group: Professional washing machines
Installation: Freestanding
Loading capacity: 9 kg
Spin speed: 1400 rpm
25
Main colour: Stainless Steel

Programs

- Heavy 90°C
- Heavy 60°C
- White wash 90°C
- White/Colour 60°C
- White/Colour 40°C
- Quick wash 60°C
- Quick wash 40°C
- Synthetic 40°C
- Wool/Hand 30°C
- Rinsing
- MOP 90°C
- MOP 60°C
- Microfibre 60°C
- Microfibre 40°C
- Disinfection 40°C
- Disinfection 60°C
- Disinfection 90°C
- Allergy cotton 60°C
- Allergy cotton 90°C
- Allergy synthetics 40°C
- Allergy synthetics 60°C
- Drum cleaning

Options

- Adjustable spin speed: No
- Super wash

Construction & Performance

- Quattro Construction™ – vibration-free spinning
- Door: Smart Seal™
- Long lasting stainless steel drum
- Active Drum™ - for a careful yet effective wash cycle.
- Heater power: 3000 W
- Precise temperature control (max deviation: +/- 1 °C)
- Water level sensor
- Drum volume: 80 l
- Drum volume (USA): 2,8 cu ft
- Brushless motor
- Payment system: Prepared
- Automatic Dosing System: Prepared external
- Shortest program time: 40 min
- Drain system: Valve

Use & flexibility

- Easy close door
- Liquid detergent insert
- Temperature range: Cold-90°C
- Door diameter: 31 cm
- Door opening angle: 180 °

Interaction & Control

- Up to 100 hours
- Remaining time indicator
- Type of display: LCD display

- 25
 - Available languages in control unit: CZ, DA, DE, EN, ES, EE, FI, FR, HR, IT, JP, LT, LV, NL, NO, PL, RU, SK, SL, SV, ZH, ZH-CN
-

Design & integration

- Door opening: Hinge on left side
 - Adjustable feet: 10 mm
 - ASKO tumble dryer can be mounted on top of the washer
 - Size 3/4" - Can be connected to hot and cold water
 - Loading position: Front
-

Safety & Maintenance

- Removable lifters for easy cleaning
 - Maximized water inlet time
 - PEX inlet hose
 - Overflow protection
 - Emergency door opening key
 - Lockable control panel
 - Unbalance detection - protects the washer against harmful vibrations.
 - Draining capacity: 20 l/min
 - Overheat protection
 - Thermal and electronic protection against overheating
-

Technical data

- G-factor: 530
 - Heater power: 3000 W
 - Drum volume: 80 l
 - Size 3/4" - Can be connected to hot and cold water
 - Counter weight material: Cast iron
 - Counter weight (kg): 10,4 kg
 - Connected load: 3200 W
 - Number of phases: 1
 - Fuse: 16 amp
 - Frequency: 50 Hz
 - Net weight: 92,5 kg
 - ISO 9001 certified manufacturer
 - ISO 14001
-

Dimensions

- Product dimensions (HxWxD): 85 × 59,5 × 70,6 cm
 - Adjustable feet: 10 mm
 - Depth with door open: 965 mm
 - Length electrical cord: 2,1 m
 - Length inlet hose: 150 cm
 - Length outlet hose: 160 cm
-

Logistic information

- Dimensions of packed product (HxWxD): 92 × 64 × 77,6 cm
 - Gross weight: 95,9 kg
 - Product code: 738165
 - EAN code: 3838782487286
 - Market: Professional
-

