Míele

PWM 520 [EL DV DD] Professional washing machine, electric heating with detergent drawer, M Touch Pro.



- Drum volume 180 I, load size 20.0 kg
- Maximum user convenience with colour touch display M Touch Pro
- Simple and safe operation thanks to automatic door lock
- Connected for the future using LAN and WiFi

EAN: 4002516435884 / Material number: 11779690 / Old Material Number: 51520001GB

Construction type and design	
Construction type	Front loader
Range	Performance
Front	Iron grey
Maximum load with a load ratio of 1:9 in kg	20.0
Load ratio	1:9
Load in kg	20.0
Drum volume in I	180
Door opening [Ø] in mm	415
Door opening angle in degrees	180
Door hinge	right
Automatic door lock	•
Innovative suds container	•
Maintenance-free motor with frequency converter	•
Patented honeycomb drum 2.0	•
Application	
Suitable for the hotel and catering industry	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in I/kg	7.80
Specific energy consumption for cold water connection in kWh/kg	0.20
Specific water consumption for hot water connection in I/kg	7.20
Specific energy consumption for hot water connection in kWh/kg	0.07
Water consumption with cold water connection in I	156.0
Energy consumption with cold water connection in kW	4.00
Programme duration in minutes with cold water connection	58
Water consumption with hot water connection in I	144.0
Energy consumption with hot water connection in kW	1.40
Programme duration in minutes with cold water and hot water connection	49
Water consumption in ECO programme with cold water connection in I	142.0
Energy consumption in ECO programme with cold water	2.60
Programme duration in minutes with cold water connection in ECO programme	41
-	•

Míele

PWM 520 [EL DV DD] Professional washing machine, electric heating with detergent drawer, M Touch Pro.



EAN: 4002516435884 / Material number: 11779690 / Old Material Number: 51520001GB

Water consumption in ECO programme with hot water connection in I	140.0
Energy consumption in ECO programme with hot water	0.60
Programme duration in minutes with cold water and hot water connection in ECO programme	36
Programme running time in minutes for Mops standard 60 °C programme with hot water connection	1.19
Residual moisture with cold rinse in %	53
Residual moisture with hot rinse in %	49
Spin speed in rpm	950
g factor	361
Tested operating hours	30000
Controls	
Programmability	programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Option to enter weight prior to start of programme	•
Standard and target group Programmes	
Basic programmes	•
Dispensing	
Detergent drawer	3 compartments
Maximum number of connections for liquid dispenser	12
pumps [number]	
Empty sensor	•
Observational all and described as a second as	
Standard electrical connection	
Heating type	Electric
	Electric 3N AC 400V 50HZ
Heating type	
Heating type Electrical connection	3N AC 400V 50HZ
Heating type Electrical connection Heater rating in kW	3N AC 400V 50HZ 15.00
Heating type Electrical connection Heater rating in kW Total connected load in kW	3N AC 400V 50HZ 15.00 16.00
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A	3N AC 400V 50HZ 15.00 16.00
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1	3N AC 400V 50HZ 15.00 16.00 25
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ 15.00
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ 15.00 16.00
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ 15.00 16.00
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ 15.00 16.00 25
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number]	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ 15.00 16.00 25 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number]	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ 15.00 16.00 25 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th.
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Dump valve Dimensions and weight	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ 15.00 16.00 25 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union DN 70
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ 15.00 16.00 25 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union DN 70
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, width in mm	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ 15.00 16.00 25 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union DN 70 1450 924
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, depth in mm	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ 15.00 16.00 25 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union DN 70 1450 924 935
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, depth in mm External dimensions, gross height in mm	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ 15.00 16.00 25 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union DN 70 1450 924 935 1585
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ 15.00 16.00 25 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union DN 70 1450 924 935 1585 1090
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ 15.00 16.00 25 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union DN 70 1450 924 935 1585 1090 1130
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ 15.00 16.00 25 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union DN 70 1450 924 935 1585 1090 1130 389.0
Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm	3N AC 400V 50HZ 15.00 16.00 25 3N AC 400V 60HZ 15.00 16.00 25 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union DN 70 1450 924 935 1585 1090 1130



PWM 520 [EL DV DD] Professional washing machine, electric heating with detergent drawer, M Touch Pro.



EAN: 4002516435884 / Material number: 11779690 / Old Material Number: 51520001GB

Emissions data	
Emission sound pressure level in the workplace	67 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	6.48
Features	
3-dimensional imbalance monitoring	•
Disinfection rinse	•
Efficient scoop-and-ladle ribs	•
Spring-in-spring system	•
Temperature monitoring	•
Special heater element	•
Automatic load control+	•
Programme selection via colour frame	•
Emergency switch-off	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	92
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
LAN	•
WiFi	•
Connector Box	•
Test certificate	
CE	•
VDE-EMC	•
VDE	•
Splash-proof safety rating IPX4	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•