

PW 6080 Vario XL [EL AV 1N AC 230V 50Hz]

Washing machine, electrically heated

with suspended drum unit, shortest programme running time of 53 min and drain valve.



- Drum volume ??, load size ??
- Large programme variety application-specific wash programmes
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 44 %^{*}, g-factor520 l

^{*} Residual moisture specification relates to a hot rinse during the last rinse cycle.

EAN: 4002516235798 / Material number: 11330440 / Old Material Number: 516080X9GB

Construction type and design	
Construction type and design	Front loodor
Construction type	Front loader
Range	Octoplus Octoplus
Front Load ratio	Octo blue
	1:9
Door opening angle in degrees	180
Door hinge	right
Maintenance-free motor with frequency converter	•
Honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for facility management	•
Suitable for launderettes	•
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for domestic use	•
Suitable for doctors' and dentists' practices	•
Performance data	
Specific water consumption for hot water connection in I/kg	8.00
Specific energy consumption for hot water connection in kWh/kg	0.05
Programme duration in minutes with cold water connection	57
Programme duration in minutes with cold water and hot water connection	53
Residual moisture with cold rinse in %	49
Residual moisture with hot rinse in %	44
Spin speed in rpm	1300
g factor	520
Tested operating hours	30000
Controls	
Control system	Profitronic L Vario
Programmability	programmable
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard and target group Programmes	
Basic programmes	•
Programmes for the hotel and catering industry	•
Programmes for retirement and care homes	•
Programmes for facility management	•



PW 6080 Vario XL [EL AV 1N AC 230V 50Hz] Washing machine, electrically heated with suspended drum unit, shortest programme running time of 53 min and drain valve.



EAN: 4002516235798 / Material number: 11330440 / Old Material Number: 516080X9GB

Programmes for launderettes	•
Programmes for residential homes and apartments	•
Programmes for dry cleaners	•
Programmes for commercial laundries	•
Programmes for small businesses	•
Programmes for fire brigades and rescue services	•
Programmes for studs, riding schools, and stables	•
Programmes for universities, nurseries, and school	•
Programmes for hospitals	•
Programmes for fast food restaurants	•
Programmes for camp sites	•
Programmes for sports clubs	•
Programmes for beauty clinics, spas, and fitness studios	•
Programmes for domestic use	•
Programmes for doctors' and dentists' practices	•
Dispensing	
Detergent drawer	3 compartments
Patented liquid dispensing adapter	•
Maximum number of connections for liquid dispenser	6
pumps [number]	
Empty sensor	•
Standard electrical connection	
Heating type	Electric
Electrical connection	AC 230V 50HZ
Heater rating in kW	5.30
Total connected load in kW	5.50
Fuse rating in A	25
Water connection/drainage	
Cold water [number]	1x 1/2" hose w/ 3/4" th.
Cold water [number]	1x 1/2" hose w/ 3/4" th. union
Cold water [number] Hot water [number]	union 1x 1/2" hose w/ 3/4" th.
Hot water [number]	union 1x 1/2" hose w/ 3/4" th. union
Hot water [number] Grey water (optional) [number]	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union
Hot water [number] Grey water (optional) [number] Dump valve	union 1x 1/2" hose w/ 3/4" th. union
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight Maximum floor loading in N	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight Maximum floor loading in N Emissions data	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70 2330
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight Maximum floor loading in N Emissions data Emission sound pressure level in the workplace	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70 2330 <70 dB(A) re 20 μPa
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight Maximum floor loading in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70 2330
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight Maximum floor loading in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70 2330 <70 dB(A) re 20 μPa
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight Maximum floor loading in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70 2330 <70 dB(A) re 20 μPa
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight Maximum floor loading in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Imbalance monitoring Disinfection rinse	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70 2330 <70 dB(A) re 20 μPa 3.00
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight Maximum floor loading in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Imbalance monitoring	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70 2330 <70 dB(A) re 20 μPa 3.00 •
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight Maximum floor loading in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Imbalance monitoring Disinfection rinse	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70 2330 <70 dB(A) re 20 μPa 3.00 • •
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight Maximum floor loading in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Imbalance monitoring Disinfection rinse Temperature monitoring	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70 2330 <70 dB(A) re 20 μPa 3.00 • •
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight Maximum floor loading in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Imbalance monitoring Disinfection rinse Temperature monitoring Special heater element	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70 2330 <70 dB(A) re 20 μPa 3.00 • • •
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight Maximum floor loading in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Imbalance monitoring Disinfection rinse Temperature monitoring Special heater element Automatic load control	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70 2330 <70 dB(A) re 20 μPa 3.00 • • • •
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight Maximum floor loading in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Imbalance monitoring Disinfection rinse Temperature monitoring Special heater element Automatic load control Flow meter	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70 2330 <70 dB(A) re 20 μPa 3.00 • • • •
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight Maximum floor loading in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Imbalance monitoring Disinfection rinse Temperature monitoring Special heater element Automatic load control Flow meter Communication slot	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70 2330 <70 dB(A) re 20 μPa 3.00 • • • • • • • • • • •
Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight Maximum floor loading in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Imbalance monitoring Disinfection rinse Temperature monitoring Special heater element Automatic load control Flow meter Communication slot Machine-independent accessories	union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70 2330 <70 dB(A) re 20 μPa 3.00 • • • • • • • • • •



PW 6080 Vario XL [EL AV 1N AC 230V 50Hz] Washing machine, electrically heated

with suspended drum unit, shortest programme running time of 53 min and drain valve.



EAN: 4002516235798 / Material number: 11330440 / Old Material Number: 516080X9GB

Connection options	
Payment system	•
Optical interface for service access	•
Serial interface module RS 232 (optional)	•
Peak load cut-out/energy management (optional)	•
Capacities	
Respirator masks [number]	4-5
Overalls [number]	1
Over jackets [number]	1-2
Synthetic duvets [number]	1
Synthetic pillows [number]	1-2
Down duvets [number]	1
Down pillows [number]	1-2
Cloths, 22 g [number]	182
Cotton mops, 40 cm / 190 g [number]	42
Cotton mops, 50 cm / 220 g [number]	36
Microfibre mops, 40 cm / 120 g [number]	66
Microfibre mops, 50 cm / 170 g [number]	47
Summer horse blankets [number]	1-2
Test certificate	
CE	•
VDE-EMC	•
VDE	•
Splash-proof safety rating IPX4	•
WRAS	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•

Complies with Machinery Directive 2006/42/EC