

Drying cabinet

DC6-10 with heat pump

Drying Cabinets have no mechanical action and are used to efficiently dry bulky items such as workwear/overalls/gloves and boots or delicate items such as silk and linen



Priority on people

Ergonomic design, with user friendly positioning of door handle, control panel and suitable for disabled users

- Easy operation with 2 automatic drying programs, which will stop once the load is dry
- Braille script
- Insulated doors for quiet operation and robust design
- 20 extensible hangers for easy loading/unloading, reversible
- Flexible installation with adjustable feet



Long-term savings

By using a Drying Cabinet with a Heat Pump, not only can you avoid exhaust connection you also achieve very low energy consumption. Comes with a built in condensing pump which can handle 0.5m pressure height



Productivity

Time saving when used instead of flat or hang drying. The door can be opened a short moment without stopping the drying process

Safety

Option to activate child safety start lock

Other

- Shelf for flat drying
- Shelf for flat drying
- Built in work light



Main specifications		DC6-10
Rated capacity	kg	10
Evaporation*	g/min	55
Drying time cotton**	min	60
Heat pump	kW	2.6
Energy/load of linen	kWh/kg	0.31
Energy/water evaporated	kWh/l	0.62

* Applies to 6.5 kg dry weight cotton with 50% residual moisture.

** The drying cabinet reconditions 5 minutes after the textiles have dried.

Electrical connection		DC6-10
Voltage 220-240V 1AC 50-60 Hz		
Traditional thread locker	kW(A)	2.6 (13)
Automatic circuit breaker	kW(A)	2.6 (13)
Refrigerant		R407C
Weight		
	net, kg	205
Sound level		
Pressure level*	dB(A)	<70
Heat emission		
Average heat emission per drying cycle used to assess ventilation need** kW		1.1
Dimensions in mm		
A	Width	1395
B	Depth	650
C	Height	1915
D		1930
E		15
F		1080
G		495
H		470
I		620
J		970
K		850
1 Operating panel 2 Condensation nipple 3 2.5 m connecting cable included		



Colour of front and side panels is silver grey and handle is dark blue.

* Sound power levels measured according to ISO 60704.

** For assistance with dimensioning necessary ventilation needs, contact authorized ventilation technician.
 For sufficient ventilation all sources introducing heat need to be taken into account plus all other parameters effecting the ventilation need. Climate zone, building parameters, room size, etc.

